

Liquid Beeswax GLEIVO 315

Application range	<p>For interior timber such as paneling and furniture that has been pre-treated with LIVOS products. Not suitable for areas exposed to water splashes.</p> <p>For regular care of linoleum. To refresh waxed timber, cork and stone surfaces, such as floors, paneling and furniture.</p>
Technical qualities	Liquid. Applicable by airless spraying. Produces a silky glossy finish when completely dry.
Full declaration	Beeswax, micronized wax, carnauba wax, pine oil, linseed oil, orange oil, isosalphates, alumina, rosemary oil and drying agents free of lead.
Colors	Clear. Coloration is possible with max. 10% of VINDO Natural Gloss Paint No. 629
Dilution	Ready to use.
Application method	Apply a very thin coat by brushing, spraying or with a wadded cloth at temperatures above 12 OC (54 OF). For surfaces treated with DELVA use a brush, roller or wadded cloth and polish after drying.
Coverage	For surface treatment: 1 liter (1.06 quart) is sufficient for approximately 25 m ² (269 ft ²), i.e. 40 ml/m ² ; could be considerably less, depending on the condition and absorbency of the surface. Always do a test application! For surface care: 1 liter (1.06 quart) is sufficient for an average of 100 m ² (1076 ft ²), i.e. 10 ml/m ² .
Cleaning	Clean equipment immediately after use with SVALOS Thinner No. 222, or LEVO Brush Cleaner No. 997.
Drying time	At 23°C (73°F) and 50% relative humidity, approximately 2 - 4 hours.
Specific gravity	0.78 g/ml.
Safety advice	Contains limonene and Cobalt (+2) salts. Can cause allergic reactions. R 53 May cause long-term adverse effects in the aquatic environment. S 2 Keep out of the reach of children. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label
Disposal	According to locally regulated laws. Packaging: Made of polyethylene (PE). This material is ground water neutral and recyclable.
Container sizes	0.25 l; 1 l; 2.5 l; 10 l; 30 l; 200 l.
Storage	Cool and dry. Please see label for expiry date. Close lid tightly after use.
Important tips	GLEIVO 315 - Liquid Beeswax
Preparation	The surface must be dry, solid, clean, and free of grease and dust. Surface must be pre-treated with LIVOS oils, e.g. MELDOS Natural Resin Hardening Oil No. 264, ARDVOS Universal Wood Oil No. 266 or LIVOS stains, such as DARIX Transparent Furniture Stain No. 297. To ensure compatibility on surfaces previously treated with products from another manufacturer, do a test application on an inconspicuous area.
Application	Shake or stir product thoroughly before use. Apply GLEIVO Beeswax No. 315 very thinly and evenly with a brush or cloth. After

approximately 2 - 4 hours, polish (by wood in the direction of the wood grain) with a wadded cloth, a wax brush or a floor polisher.

Cleaning

Remove dust with a vacuum cleaner or mop.

Rubber abrasion and stubborn dirt can be removed with SVALOS Thinner No. 222. Clean with TRENA pH-Neutral Cleaner No. 556 according to demand.

Care

According to usage, apply an after-treatment with GLEIVO Beeswax No. 315 or with BIVOS Oil Wax No. 375 once or twice a year.

Important tips

Ensure good ventilation during application and drying times.

A very thin coating of beeswax on surfaces with a high electrostatic charge (artificial resin varnishes, etc.) will significantly reduce static electricity on those surfaces.

On surfaces coated with DELVA Smooth Render No. 426, GLEIVO No. 315 protects against abrasion and dirt. GLEIVO delays the possible bleaching of the DELVA plant pigments and results in a brilliant, silky gloss to enhance the character of the colors.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.