

Wall & Ceiling Paint ALBION 407

Range of application	For plaster, concrete, masonry, oatmeal wallpaper, gypsum board as well as sound water-based painted surfaces. Not suitable for textile or vinyl wallpaper.
Technical qualities	Solvent free according to the ECO Label. White, wipe-able, highly water vapor permeable, antistatic (dust resistant), easy to use. Does not tend to drip or splash. DIN 55 987 certified for coverage strength. Coloration possible with URA Coloring Paste No. 410 at any ratio.
Full declaration	Water, chalk, talcum, natural resins, titan dioxide, methyl cellulose, beeswax soap, hemp oil, safflower oil, orange oil, silver chloride, proteins and Isoaliphates. Solvent content less than 2%.
Color	White.
Application method	Stir well. Do not dilute. Apply with a brush or lambs-wool roller at temperatures above 10°C (50°F).
Coverage	1 liter (1.06 fl. quart.) is sufficient for approximately 8 m ² (86 ft ²) per coat, i.e. 125 ml/ m ² . Could be considerably less or more depending upon the condition and absorbency of the surface. A test coat is recommended.
Drying time	At 23°C (73.4°F) and 50% relative humidity, approximately 12 hours.
Specific gravity	Approximately 1.26 g/ml
Cleaning up	Clean tools immediately after use with warm water and LATIS Tool Cleaner No. 558.
Disposal	According to locally regulated laws.
Container sizes	1 l; 2.5 l; 10 l.
Storage	Cool and dry, protected from frost and freezing. Use contents of opened containers within 2-3 days. Please, see label for expiration date.

How to use **ALBION 407 Wall & Ceiling Paint**

General surface	Surface must be dry, able to absorb and bear load, neutral, clean, and free of separation agents, dirt, grease, cracks, efflorescences and fungi. Fill holes and cracks with VEDO Filler No. 440. Smooth out before painting. Repair construction or structural cracks with crack-bridging repair system. The following summary contains information on priming various surfaces, as well as tips on when to use GRAVA Wall Primer/Sealer No. 408. GRAVA must be diluted enough so that no visible film develops; as a general rule, dilute with water at ratios between 1:1 and 1:2. Testing on the surface to be primed before beginning is recommended. Surface Preparation Primer Cement Remove dust and dirt GRAVA Gypsum/lime plaster, drywall Remove dust and dirt; sand off GRAVA powder coatings Concrete Remove oil residue, dust, dirt GRAVA Breeze block Remove dust and dirt; use filler GRAVA if necessary Clay, brick masonry Remove dust and dirt GRAVA Old chalky paint Brush with a wire brush and remove GRAVA dust Old oil, acrylic or latex paint Roughen surface and remove dust None or wash with alkaline and rinse well Peeling paint or distemper Remove thoroughly, wash well and GRAVA let dry Hardboard Remove dust, dirt, grease None Wood veneer, chipboard Remove dust and dirt GRAVA Gypsum fiberboard Check joints for fit and tightness GRAVA Oatmeal or other natural wallpaper Check that glue holds paper to wall None (except textile) and re-glue if necessary
------------------------	--

Important tips

Stir product thoroughly before using. A test coat is recommended. There might be additional coats of DUBRON Wall & Ceiling paint No. 407 necessary if the surface is high-contrast, very smooth, strong or differently absorbing. Application with an airless spraying device is particularly advantageous when the surface is very smooth or high-contrast. If the coats applied exceed to amount of coverage recommended the wipe-ability is reduced and the dried paint will tend to appear chalky. Remove drips immediately with SVALOS Dilutant No. 222. ALBION Wall and Ceiling Paint can be mixed with URA Coloring Paste No. 410 in any ratio. Confirm color/tint once test coat is dry. Added concentration of URA No. 410 can reduce the wipe-ability. Warning: Do not mix with tints from other manufacturers.

LIVOS products contain organically sourced ingredients and are never tested on animals. These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.